

PRODUCT DATASHEET

Item No. 40025 – Medio Line 25N, d= 0.2N

| Description | |
|--|--|
| <p>Precise and handy Spring Balance with durable anodised aluminium tube and long scale of high resolution. Tare and zero adjustment. Swivelable, rotatable and removable suspension bow, guided in a ring. Lower suspension swivels, rotates and can be easily changed using different accessories. Measurement of breaking forces up to 1000 g (optional drag pointer no. 4.012 recommended). A multifunctional long life measuring instrument for weighing and measuring traction forces. Optional pressure measurement with accessory – two functions in one instrument. Always ready for use, needs no batteries. A time-tested original Swiss quality product.</p> | |

| Technical Data | |
|------------------------------|---------------------------------------|
| Capacity | 25N |
| Division | 0.2N |
| Color | bordeaux |
| Precision | +/- 0.3% |
| Tare (zero adjustment) | ~ 20% |
| Exchange of lower suspension | "click and go" system |
| Standard Suspension | Hook |
| Components | non-corroding (spring only protected) |
| Net weight | 38 g |
| Gross weight | 52 g |
| Measuring position | free choice |
| Calibration by user | not applicable (only by manufacturer) |
| Packaging | transparent designer case |
| Manual | DE/EN/FR/IT/ES/PT/NL |
| Warranty | 3 years |
| Code EAN13 | 7612348400256 |
| Customs Tarif | 8423.8190 |
| Country of origin | Switzerland (CH) |

| Dimension | |
|--------------------------|--------|
| S (Scale length) | 100 mm |
| L0 (Length without load) | 225 mm |
| Lm (Maximum length) | 325 mm |
| Ø (Diameter) | 12 mm |

